

Topping Spreader TS 5000

Ensuring accurate and even application of dryshake topping with the TS500 Topping Spreader. Combining high productivity and operator comfort with the latest technological adaptations to provide an emission compliant machine to the latest Tier 4 and Stage V emission level standards.

Ultimate efficiency in dryshake application

Main advantages

- Accurate application of dryshake
- Increased productivity
- Spreader head – in/out movement
- Automatic mode for easy operation
- Large material capacity
- Standard parts/components
- Easy to transport by container/lorry
- Touchscreen control
- Individual operator access codes



Specifications subject to change without notice Non contractual photo

Technical description

Specifications	
Width	2.2 m
Length	5.2 m
Height	2.4 m
Weight	8 tons
Boom reach	6.3 m
Boom head width	1.8m
Steering	2-4 wheels / Crab
Transport dimension	Standard
Bin Capacity	2.5 tons
Head bin capacity	320 kg

Engine	
Brand	HATZ
Model	4H50TIC
Emission compliance	EPA Tier 4 Final
Power	55 KW @ 2800 RPM
Torque	240 nm @ 1600 2600 RPM
Fuel	Diesel

Health & environment	
Catalytic - DOC	Yes
Diesel particle filter	On request
Eco oil	On request
Central greasing system	On request